

TOSHIBA

IK-DP20A

DAY/NIGHT PTZ DOME CAMERA



IK-DP20A
Shown with optional
pendant housing JK-PH0
and wallmount JK-WM

IK-DP20A
Shown with optional
in-ceiling housing JK-H01A



*IK-DP20A cameras integrate
with Toshiba Surveillix®
DVRs with a simple two wire
DIRECT CONNECTION!*



Lease This Product Call
800-207-8362

- **NEW** Quick Connect "Snap In" Dome Drive
- **NEW** Privacy Masking (8 Zone)
- **NEW** 92° Tilt
- IR Sensitive
- .01 Lux Day/Night Camera
- 480 line horizontal resolution
- 216X Zoom – 18X Optical, 12X Digital
- Easy to install, programmable dome camera available with pendant or in-ceiling mounts
- Focal length: f=4.1mm to 73.8mm
- Auto focus & auto iris with manual overrides
- 24V AC line lock
- 64 presets
- Auto flip 180° rotation for continuous viewing of subject as they pass underneath camera
- Variable scan speeds with high acceleration rate and steady motion
- 360° Continuous Pan Rotation
- Indoor/Outdoor Options
- Up to 255 domes can be connected in one system
- Telecom Grade Gas-Filled Surge Arrestor Technology: By incorporating a surge suppression circuit, the camera is protected against surges such as Electrostatic Discharge (ESD), lightning, and AC induction
- 3 Year Warranty

IK-DP20A

Day/Night PTZ Dome Camera

Toshiba's new quick connect "Snap In" drive makes installation easier than ever!

Toshiba IK-DP20A CCTV Dome Cameras take the hassle out of installation. They're exceptionally easy to install and even easier to integrate, with simple electrical connections, and in-ceiling or pendant mounts. The cameras offer a privacy mask, high-resolution (480 TV lines) capture, auto focus with manual over-ride, 18x optical/12x digital zoom, 92° tilt, 360° pan rotation, plus they are fully programmable with RS-422 connectivity to link up to 255 cameras on one system. In addition, the 50dB s/n video signal is perfectly suited for digital video recording.

OVERALL

- Operation Temperature
 - 0° to 50°
- Preservation Temperature
 - -20° to 60°
- Weight
 - 1.8kg
- Dimensions
 - 134mm x D x 223.7mm
- Power Supply
 - AC24±10% 60Hz
- Power Consumption
 - 35W

CAMERA

- Image Sensor
 - 1/4 IT CCD
- Day/Night Imaging
 - Yes
- Effective Pixels
 - 768(H) x 494(V)
- Lens
 - 18x Zoom, f=4.1 to 73.8mm (F1.4 to F3.0)
- Digital Zoom
 - 12x (216x with optical zoom)
- Angle of View
 - approximately 48° (wide) and approximately 2.7° (tele)
 - Privacy Mask (8 Zone)

- Minimum Illumination
 - 0.01 lux
- Horizontal Resolution
 - 480 TVL
- S/N Ratio
 - more than 50dB
- Auto Electronic Shutter
 - 1/4 to 1/10000 sec.
- Manual Electronic Shutter
 - 1 to 1/10000 sec.
- ATW White Balance
 - Auto: 3,000K - 7,500K
 - ATW: 2,000K - 10,000K One Push WB
- Gain
 - Auto
- AE Control
 - Full Auto, Shutter Priority, Manual
- Back Light Comp.
 - On/Off
- Auto Slow Shutter
 - On/Off (On Max 1/4 sec.)
- Focusing System
 - Auto, Interval, Zoom Trigger, Manual
- Video Output
 - NTSC, VBS: 1.0Vp-p (sync Negative), 75ohm

MECHANICAL

- Pan Range
 - 360° Continuous
- Tilt Range
 - 92°
- Manual Pan Speeds
 - 0.1° to 90°/s
- Manual Pan Speeds (Turbo Mode)
 - 150°/s
- Manual Tilt Speeds
 - 0.1° to 45°/s
- Preset Speeds
 - Pan: 300°/s
 - Tilt: 200°/s
- Proportional P/T
 - Provided

REMOTE CONTROL I/F

- RS-422 (receive only) Protocol
- Toshiba-P/D (Dip sw selectable)
- Bit Rate
 - 2400, 4800, 9600bps (Dip sw selectable)

1-2-3 CONFIGURATION SELECTION GUIDE

1 Select Camera
IK-DP20A Dome Camera

2 Select Housing
JK-PHO Exterior Pendant with Heater and Blower
JK-PHOT Exterior Pendant (Tinted) with Heater and Blower
JK-PHI Interior Pendant
JK-PHIT Interior Pendant (Tinted)
JK-H01A Interior In-Ceiling

3 Select Mount
Mount options for the JK-PHO/JK-PH1
JK-WM Wall mount for all pendant housing types
JK-CMA Corner mount adapter for JK-WM
JK-PMA Pole mount adapter for JK-WM
JK-PM Parapet mount for all pendant housing types
JK-CTA Ceiling mount Adapter

Example #1: System for Exterior Wall Application

- IK-DP20A Camera
- JK-PHO Exterior Pendant housing with Heater/Blower
- JK-WM Wall Mount

Example #2: System for Exterior Pole Mount Application

- IK-DP20A Camera
- JK-PHO Exterior Pendant housing with Heater/Blower
- JK-WM Wall Mount
- JK-PMA Pole Mount Adapter

Example #3: System for Interior Drop Ceiling

- IK-DP20A Camera
- JK-HC01A In-Ceiling Housing
- JK-CTA 2x2 Ceiling Tile Adapter (optional item replaces 2x2 ceiling tile)

COMPONENT SELECTION GUIDE

Controllers



VCL485
Universal
Controller

Housings



JK-H01A
In-Ceiling
Housing



JK-PHO/JK-PHI
Indoor/Outdoor
Pendant Housing

Mounting Brackets and Accessories



JK-PMA
Pole Mount
Adapter



JK-WM
Wall Mount



JK-CMA
Corner Mount
Adapter



JK-PM
Parapet Mount

JK-PHO
Outdoor
Housing-Clear

JK-PHOT
Outdoor
Housing-Tint

JK-PHI
Indoor
Housing-Clear

JK-PHIC
Indoor
Housing-Tint

JK-CTA
2x2 In-Ceiling
Adapter (not
shown)

DAISYCHAIN CONFIGURATIONS

